

**M61SE/M81SE/M101SE/M69SE**

Power Handling	150 Watts	170 Watts	250 Watts	150 Watts
Voice Coil	32.5 mm(1.3in)	38.6 mm(1.5in)	44.4 mm(1.75in)	38.6 mm(1.5in)
Frequency Range	97-20000 Hz	101-18000 Hz	94-15000 Hz	98-17000 Hz
Sensitivity(1W/1M)	96 dB	96 dB	98 dB	95 dB
Impedance	4 Ω	4 Ω	4 Ω	4 Ω
Magnet	35 Oz	40 Oz	47 Oz	40 Oz

**M60SQL/M80SQL**

Power Handling	150 Watts	150 Watts	100 Watts	150 Watts
Voice Coil	38.6 mm(1.5in)	38.6 mm(1.5in)	38.6 mm(1.5in)	38.6 mm(1.5in)
Frequency Range	99-13000 Hz	97-18000 Hz	113-6000 Hz	72-6000 Hz
Sensitivity(1W/1M)	97.5 dB	97 dB	93 dB	95 dB
Impedance	4 Ω	4 Ω	8 Ω	8 Ω
Magnet	22 Oz	22 Oz	20 Oz	20 Oz

6FE100/8FE100**MD40N1/MD50N1**

Power Handling	60 Watts	80 Watts	Power Handling	80 Watts
Voice Coil	38.6 mm(1.5in)	38.6 mm(1.5in)	Voice Coil	38.6 mm(1.5in)
Frequency Range	173-18000 Hz	176-16000 Hz	Frequency Range	126-15000 Hz
Sensitivity(1W/1M)	92 dB	94 dB	Sensitivity(1W/1M)	94.5 dB
Impedance	4 Ω	4 Ω	Impedance	4 Ω
Magnet	Neodymium	Neodymium	Magnet	Neodymium

MD65N1**M61BU/M81BU**

Power Handling	150 Watts	170 Watts	Power Handling	150 Watts
Voice Coil	38.6 mm(1.5in)	38.6 mm(1.5in)	Voice Coil	38.6 mm(1.5in)
Frequency Range	124-12000 Hz	97-10000 Hz	Frequency Range	92-14000 Hz
Sensitivity(1W/1M)	95 dB	96 dB	Sensitivity(1W/1M)	95 dB
Impedance	4 Ω	4 Ω	Impedance	4 Ω
Magnet	40 Oz	40 Oz	Magnet	40 Oz

M69BU**MD65G1/MD80G1**

Power Handling	100 Watts	180 Watts	Power Handling	120 Watts
Voice Coil	38.6 mm(1.5in)	50.5 mm(2in)	Voice Coil	38.6 mm(1.5in)
Frequency Range	100-10000 Hz	100-9000 Hz	Frequency Range	100-10000 Hz
Sensitivity(1W/1M)	94dB	94 dB	Sensitivity(1W/1M)	96 dB
Impedance	4 Ω	4 Ω	Impedance	4 Ω
Magnet	23 Oz	40 Oz	Magnet	23 Oz

MD69G1**MD40N2/MD50N2**

Power Handling	60 Watts	80 Watts	Power Handling	80 Watts
Voice Coil	38.6 mm(1.5in)	38.6 mm(1.5in)	Voice Coil	38.6 mm(1.5in)
Frequency Range	175-16000 Hz	189-16000 Hz	Frequency Range	125-14000 Hz
Sensitivity(1W/1M)	90 dB	90 dB	Sensitivity(1W/1M)	91 dB
Impedance	4 Ω	4 Ω	Impedance	4 Ω
Magnet	Neodymium	Neodymium	Magnet	Neodymium

MD65N2**M61SE NEO/M81SE NEO**

Power Handling	180 Watts	225 Watts	Power Handling	200 Watts
Voice Coil	38.6 mm(1.5in)	38.6 mm(1.5in)	Voice Coil	38.6 mm(1.5in)
Frequency Range	120-15000 Hz	96-18000 Hz	Frequency Range	96-18000 Hz
Sensitivity(1W/1M)	97 dB	97.5 dB	Sensitivity(1W/1M)	97 dB
Impedance	4 Ω	4 Ω	Impedance	4 Ω
Magnet	Neodymium	Neodymium	Magnet	Neodymium

M69SE NEO**ND65XT/ND80XT**

Power Handling	200 Watts	200 Watts	Power Handling	150 Watts
Voice Coil	50.5 mm(2in)	50.5 mm(2in)	Voice Coil	38.6 mm(1.5in)
Frequency Range	102-10000 Hz	92-12000 Hz	Frequency Range	95-8000 Hz
Sensitivity(1W/1M)	97 dB	97 dB	Sensitivity(1W/1M)	96 dB
Impedance	4 Ω	4 Ω	Impedance	4 Ω
Magnet	Neodymium	Neodymium	Magnet	34 Oz

PPS4-6/PPS4-8**CX65XT/CX80XT**

Power Handling	150 Watts	200 Watts	Power Handling	120 Watts
Voice Coil	38.6 mm(1.5in)	60.6mm(2.5in)	Voice Coil	38.6 mm(1.5in)
Frequency Range	90-20000 Hz	90-20000 Hz	Frequency Range	90-20000 Hz
Sensitivity(1W/1M)	92 dB	99 dB	Sensitivity(1W/1M)	91 dB
Impedance	4 Ω	4 Ω	Impedance	4 Ω
Magnet	Neodymium	Neodymium	Magnet	40 Oz

CVX651/CVX801**M61AC/M67AC/M67AC PRO/M67AC NEO**

Power Handling	170 Watts	250 Watts	250 Watts	250 Watts
Voice Coil	38.6 mm(1.5in)	44.4 mm(1.75in)	44.4 mm(1.75in)	44.4 mm(1.75in)
Frequency Range	127-18000 Hz	137-13000 Hz	109-12000 Hz	107-15000 Hz
Sensitivity(1W/1M)	97 dB	99 dB	97 dB	99 dB
Impedance	4 Ω	4 Ω	4 Ω	4 Ω
Magnet	47 Oz	47 Oz	47 Oz	Neodymium

**MG506X/MG508X**

Power Handling	150 Watts	200 Watts	Power Handling	300 Watts
Voice Coil	50.5 mm(2in)	75.5 mm(3in)	Voice Coil	75.5 mm(3in)
Frequency Range	108-14000 Hz	79-4000 Hz	Frequency Range	65-5000 Hz
Sensitivity(1W/1M)	95dB	96 dB	Sensitivity(1W/1M)	97 dB
Impedance	8Ω	8 Ω	Impedance	8 Ω
Magnet	44 Oz	60Oz	Magnet	113 Oz

MG510X**CX61SL/CX81SL**

Power Handling	170 Watts	170Watts	Power Handling	170 Watts
Voice Coil	38.6 mm(1.5in)	38.6 mm(1.5in)	Voice Coil	38.6 mm(1.5in)
Frequency Range	133-20000 Hz	100-20000 Hz	Frequency Range	104-20000 Hz
Sensitivity(1W/1M)	97 dB	96 dB	Sensitivity(1W/1M)	96dB
Impedance	4 Ω	4 Ω	Impedance	4 Ω
Magnet	40 Oz	40 Oz	Magnet	40 Oz

CX69SL


65FH24/8FH24
69FH24

Power Handling	120 Watts	150 Watts	Power Handling	150 Watts
Voice Coil	38.6 mm(1.5in)	38.6 mm(1.5in)	Voice Coil	38.6 mm(1.5in)
Frequency Range	125-20000 Hz	119-20000 Hz	Frequency Range	110-20000 Hz
Sensitivity(1W/1M)	93 dB	92 dB	Sensitivity(1W/1M)	93 dB
Impedance	4 Ω	4 Ω	Impedance	4 Ω
Magnet	33 Oz	33 Oz	Magnet	33 Oz


MX65G1/MX80G1
MX69G1

Power Handling	100 Watts	180 Watts	Power Handling	120 Watts
Voice Coil	38.6 mm(1.5in)	50.5 mm(2in)	Voice Coil	38.6 mm(1.5in)
Frequency Range	110-20000 Hz	100-20000 Hz	Frequency Range	100-20000 Hz
Sensitivity(1W/1M)	94 dB	95 dB	Sensitivity(1W/1M)	95 dB
Impedance	4 Ω	4 Ω	Impedance	4 Ω
Magnet	23 Oz	40 Oz	Magnet	23 Oz


XW151/XW181
XW152/XW182

Power Handling	4500 Watts	5000 Watts	Power Handling	5000 Watts	6000 Watts
Voice Coil	100 mm(4in)	100 mm(4in)	Voice Coil	114 mm(4.5in)	127 mm(5in)
Frequency Range	38-800 Hz	30-800 Hz	Frequency Range	40-800 Hz	35-800 Hz
Sensitivity(1W/1M)	89 dB	87 dB	Sensitivity(1W/1M)	88 dB	87 dB
Impedance	4+4 Ω	4+4 Ω	Impedance	4+4 Ω	4+4 Ω
Magnet	412 Oz	412 Oz	Magnet	464 Oz	464 Oz


12SUB4000/15SUB4000/18SUB4000

Power Handling	3000 Watts	4000 Watts	4500 Watts
Voice Coil	75.5 mm(3in)	100 mm(4in)	100 mm(4in)
Frequency Range	60-1500 Hz	52-1200 Hz	45-1000 Hz
Sensitivity(1W/1M)	87 dB	88 dB	88 dB
Impedance	4+4 Ω	4+4 Ω	4+4 Ω
Magnet	301 Oz	548 Oz	548 Oz

Our range of products covers
Subwoofer
Midrange Speaker
Coaxial Speaker
Super Tweeter



Facebook: chinesemraudio
 Email: info@chinesemraudio.com
 Whatsapp: +86 1770688 8050
 www.chinesemraudio.com

29 B Intelligent Manufacturing Industrial Park,
 Liando U Valley, Yinzhou, Ningbo, China

**This Is Where
 Roar Happens**

MasRoar Chinese Mr Audio

Massive Energy. One Roar.